

Phone: 916.683.7111  
Fax: 916.691.941

Web: [www.elkgrovecity.org](http://www.elkgrovecity.org)

8401 Laguna Palms Way  
Elk Grove, California 95758



## City of Elk Grove Signing & Striping Notes

1. SIGNING AND STRIPING NOTES REFER TO THE LATEST VERSION OF THE CITY STANDARD SPECIFICATIONS, WHICH REFERENCE CALTRANS STANDARD PLANS, STATE STANDARD SPECIFICATIONS (SSS), AND TRAFFIC MANUAL. ANY REFERENCES REGARDING THE TRAFFIC CONTROL DEVICE TOPICS IN THE TRAFFIC MANUAL ARE SUPERSEDED AND REPLACED BY THE FEDERAL MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) 2003 EDITION AS AMENDED BY THE MUTCD 2003 CALIFORNIA SUPPLEMENT. ALL SIGNING AND STRIPING WORK SHALL COMPLY WITH THESE STANDARDS.
2. THE DEVELOPER OR CONTRACTOR SHALL BE RESPONSIBLE FOR ADDITIONAL SIGNING AND STRIPING, AS DETERMINED BY THE CITY OF ELK GROVE FOR PUBLIC SAFETY.
3. ALL EXISTING SIGNING THAT CONFLICTS WITH PROPOSED SIGNING SHALL BE REMOVED.
4. ALL SIGNS SHALL BE STANDARD SIZE UNLESS OTHERWISE NOTED.
5. ALL PARKING RESTRICTION SIGNS SHALL HAVE ENGINEERING GRADE REFLECTIVE SHEETING. ALL OTHER SIGNS SHALL HAVE DIAMOND GRADE CUBED REFLECTIVE SHEETING.
6. NEW SIGNS SHALL BE INSTALLED ON STREET LIGHT POLES OR 2" DIAMETER TUBULAR GALVANIZED STEEL POSTS WITH VANDAL-RESISTANT HARDWARE. THE POSTS SHALL BE SET IN CONCRETE. ONE OR MORE SIGN PANELS MOUNTED ON A SINGLE SIGN POST OR STREET LIGHT POLE SHALL BE COUNTED AS ONE ROADSIDE SIGN INSTALLATION UNLESS OTHERWISE NOTED.
7. SIGNS SHALL BE MOUNTED SO THAT THE BOTTOM OF THE SIGN IS AT LEAST SEVEN FEET FROM THE FINISHED GRADE IN AREAS WHERE PEDESTRIANS MAY BE PRESENT, EVEN IF THERE IS NO SIDEWALK. TO SATISFY THIS REQUIREMENT, EXISTING POSTS MAY HAVE TO BE REPLACED IF ADDITIONAL SIGNS ARE ADDED.
8. WHERE POSSIBLE, AT LEAST TWO FEET OF CLEARANCE SHOULD BE PROVIDED FROM CURB FACE TO EDGE OF SIGN.
9. ALL PERMANENT STRIPING AND PAVEMENT MARKINGS SHALL BE THERMOPLASTIC UNLESS OTHERWISE NOTED. YELLOW THERMOPLASTIC SHALL BE LEAD-FREE ORGANIC MATERIAL. CURB MARKINGS SHALL BE PAINT.
10. ALL STRIPING AND MARKINGS SHALL BE REFLECTORIZED UNLESS OTHERWISE DIRECTED.
11. ALL EXISTING STRIPING AND MARKINGS THAT CONFLICT WITH PROPOSED STRIPING AND MARKINGS SHALL BE REMOVED BY WET SANDBLASTING OR GRINDING. PAVEMENT LEGENDS AND ARROWS THAT ARE REMOVED SHALL BE REMOVED IN A BLOCK PATTERN. ALL STRIPING AND MARKING REMOVAL AREAS SHALL BE TREATED WITH AN APPROVED PAVEMENT SEALER.
12. ALL MEDIAN ISLAND NOSE CURB FACES FROM BC (BEGIN CURVE) TO EC (END CURVE) SHALL BE PAINTED WITH YELLOW OR WHITE REFLECTIVE PAINT. ONE-WAY YELLOW OR WHITE REFLECTIVE PAVEMENT MARKERS SHALL ALSO BE INSTALLED ON TOP OF ALL MEDIAN ISLAND NOSE CURBS AND POSITIONED TO FACE ON-COMING TRAFFIC.

Phone: 916.683.7111  
Fax: 916.691.941

Web: [www.elkgrovecity.org](http://www.elkgrovecity.org)

8401 Laguna Palms Way  
Elk Grove, California 95758



13. BLUE REFLECTIVE PAVEMENT MARKERS SHALL BE PLACED ACROSS FROM ALL FIRE HYDRANTS.